

|                     |                  |
|---------------------|------------------|
| <b>Product Name</b> | <b>EV Series</b> |
| <b>Model No.</b>    | <b>EV-5922E</b>  |

**Specifications**

1. Body & Door constructed from 12-gauge steel exterior.
2. Over 3/4 inch (.84) of steel between door and lock, including hardplate.
3. Body has a total of 2 pieces of 1/2 inch fire board for a total of 1 inch fire board.
4. Door has a total of 3 pieces of 1/2 inch fire board for a total of 1 1/2 inches fire board.
5. Door has fire-activated expanding door seal located on the door-frame on all four sides.
6. A total of 2 mounting holes sized 7/16 inch in diameter and are located on all 4 sides of the door.
7. Dehumidifier access hole in 7/16 inch in diameter and located on the lower right hand corner of the back wall. Note that the fire board is not pre-drilled.
8. The interior of the safe, the shelves and the door back cover are all upholstered.
9. Interior shelving are upholstered wood.
10. Safe is built to U.L. RSL standards
11. Safe has a manufacturer's certified fire rating of 1 hour at 1200 degrees.

\* EV SERIES AVAILABLE IN BLACK, WHITE & RED

| <b>External Dimensions</b> | <b>Internal Dimensions</b> | <b>Weight</b> | <b>Rifles</b> |
|----------------------------|----------------------------|---------------|---------------|
| <b>H X W X D (Inch)</b>    |                            | <b>(Lbs.)</b> |               |
| 59 x 22 x 16               | 56.5 x 19.5 x 12.5         | 385           | 16            |



*Protecting Canadians Coast to Coast*